

LOW)

mm

± 0.1

06T-016L	1.6A	●	●	0.156
06T-020L	2A	●	●	0.265
06T-025L	2.5A	●	●	0.453
06T-030L	3A	●	●	0.952
06T-032L	3.15A	●	●	0.990
06T-035L	3.5A	●	●	1.16
06T-040L	4A	●	●	1.38
06T-050L	5A	●	●	2.53

DENOTES FOR APPROVED

L1 DENOTES FOR 32V	L1	32V
L2 DENOTES FOR 63V	L2	63V

ELECTRICAL CHARACTERISTICS/ :


% of CURRENT RATING 额定电流的 %	BLOWING TIME 熔断时间	
100%	4 hours Min.	最快 4 小时
200%	1 second Min. 120 seconds Max.	最快 1 秒 最慢 120 秒
300%	0.05 seconds Min. 3 seconds Max.	最快 0.05 秒 最慢 3 秒
800%	0.0005 seconds Min. 0.05 seconds Max.	最快 0.0005 秒 最慢 0.05 秒

PACKING/

5,000 PIECES TAPED AND REELED IN ONE BOX

5,000

BOX SIZE/



Standards/ UL 248-1, UL 248-14

Operating Temperature/ -55 -125

Storing Temperature/ -55 -85

Resistance to soldering heat/ 260 10s Max.

Solderability/ 235 ± 5 , 3.5s+0.5/-0s

**06T AVERAGE I-T CHARACTERISTICS CURVE
(FOR REFERENCE ONLY)**

06T I-T ()

TIME(s)/ 时间 (秒)

CURRENT(A)/ 电流 (安培)