

Φ2.4x7mm, RoHS Compliant & Pb-Free
MICROFUSE (SLOW-BLOW)

TECHNICAL PARAMETERS/ :

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证								REFERENCE (A ² ·Sec.) (RoHS) IT 参考值	
		CCC		UR(cUR)		CSA		TÜV			PSE
		H	L	H	L	H	L	H	L		L
20T-0375H/L	375mA			●	●	●	●				0.1614
20T-0400H/L	400mA			●	●	●	●				0.1713
20T-0500H/L	500mA	●		●	●	●	●	●	●		0.3374
20T-0600H/L	600mA			●	●	●	●	●	●		0.4662
20T-0630H/L	630mA	●		●	●	●	●	●	●		0.4890
20T-0750H/L	750mA			●	●	●	●	●	●		0.7074
20T-0800H/L	800mA	●		●	●	●	●	●	●		0.8908
20T-010H/L	1A	●		●	●	●	●	●	●	●	1.916
20T-012H/L	1.2A			●	●	●	●	●	●	●	2.061
20T-013H/L	1.25A	●		●	●	●	●	●	●	●	2.139
20T-015H/L	1.5A			●	●	●	●	●	●	●	3.982
20T-016H/L	1.6A	●		●	●	●	●	●	●	●	4.191
20T-020H/L	2A	●		●	●	●	●	●	●	●	7.803
20T-025H/L	2.5A	●		●	●	●	●	●	●	●	11.95
20T-030H/L	3A			●	●	●	●			●	14.11
20T-032H/L	3.15A	●		●	●	●	●			●	18.62
20T-035H/L	3.5A			●	●	●	●			●	20.89
20T-040H/L	4A	●		●	●	●	●			●	31.89
20T-050H/L	5A	●		●	●	●	●			●	39.51
20T-060H/L	6A			●	●	●	●				65.06
20T-063H/L	6.3A	●		●	●	●	●				68.31
20T-070H/L	7A			●	●	●	●				72.91

DENOTES FOR APPROVED

H DENOTES FOR 250V H 250V


L DENOTES FOR 125V L 125V

ELECTRICAL CHARACTERISTICS/ :

% of CURRENT RATING 额定电流的 %	BLOWING TIME 熔断时间	
100%	4 hours Min.	最快 4 小时
200%	1-60 seconds	1-60 秒
300%	0.2-3 seconds	0.2-3 秒
800%	0.02-0.1 second	0.02-0.1 秒

PACKING/

1. INNER BOX/ : AMMO PACK



2. OUTER CARTON/ : 10 INNER BOXES / CARTON

CARTON SIZE / L440x W270x H230(mm)

INTERRUPTING CAPACITY /

30 amperes at 125V AC (100mA-7A)

30 amperes at 250V AC (100mA-7A)

100 amperes at 125V AC (1A-5A) PSE

Dimensions/ :

Standards/ UL 248-1, UL 248-14

Operating Temperature/ -55 ~-125

Storing Temperature/ -55 ~-85

Resistance to soldering heat/ 260 10s Max.

Solderability/ 245 ± 5 , 5s± 0.5s

20T AVERAGE I-T CHARACTERISTICS CURVE
(FOR REFERENCE ONLY)

20T I-T ()

TIME(s)/ 时间(秒)

CURRENT(A)/ 电流(安培)