

Φ5.2x20mm RoHS Compliant & Pb-Free
CERAMIC TUBE FUSE (TIME-LAG)

BREAKING CAPACITY/

TECHNICAL PARAMETERS/

PART NO. 目录编号	CURRENT RATING 额定电流	MAX. VOLTAGE DROP 最大电压降 (mv)	SAFETY APPROVALS 安全认证		REFERENCE (A ² .Sec.) (RoHS) I ² T 参考值
			cURus	TÜV	
5HT-020H	2A	190	●	●	7.952
5HT-025H	2.5A	180	●	●	9.746
5HT-032H	3.15A	140	●	●	10.24
5HT-040H	4A	100	●	●	22.48
5HT-050H	5A	100	●	●	33.52
5HT-063H	6.3A	100	●	●	68.18
5HT-080H	8A	100	●	●	73.46
5HT-100H	10A	100	●	●	123.2
5HT-120H	12A	80	●	●	234.1
5HT-125H	12.5A	80	●	●	272.2
5HT-150H	15A	80	●	●	349.1
5HT-160H	16A	80	●	●	445.2
5HT-200H	20A	80	○	○	
5HT-250H	25A	80	○	○	

DENOTES FOR APPROVED
 ○ DENOTES FOR PENDING ○
 H DENOTES FOR 500V H 500V
 H₁ DENOTES FOR 400V H₁ 400V
 H₂ DENOTES FOR 600V H₂ 600V

Standards/ IEC 60127 GB 9364
 Operating Temperature/ -55 ~125
 Storing Temperature/ -55 ~85
 Resistance to soldering heat/ 260 10s Max
 Solderability/ 245 ± 5 , 5s± 0.5s

ELECTRICAL CHARACTERISTICS/

RATING 额定		BLOWING TIME 熔断时间		
		2A-3.15A	4A-10A	>10A
2.1In	Max. 最慢	30 minutes	30 minutes	30 minutes
	Min. 最快	750 ms	750 ms	1 second
2.75In	Max. 最慢	80 seconds	80 seconds	80 seconds
	Min. 最快	95 ms	150 ms	150 ms
4In	Max. 最慢	5 seconds	5 seconds	8 seconds
	Min. 最快	10 ms	10 ms	20 ms
10In	Max. 最慢	150 ms	150 ms	150 ms