



NH2XLaR 1500V DC 125-420A

Class of Operation: aR

保护特性: aR

Standard/ UL 248-13, IEC 60269-4, GB/T 13539.4

INTERRUPTING CAPACITY/
250,000 A at 1500V DC (Time Constant: ≤ 4ms)

NH2XLaR 1500V 平均 I-T 曲线图 (仅供参考)

NH2XLaR 1500V AVERAGE I-T CHARACTERISTICS CURVE
(FOR REFERENCE ONLY)

TECHNICAL PARAMETERS/ :

PART NO. 目录编号	CURRENT RATING 额定电流	SAFETY APPROVALS 安全认证	
		cURus	CE
2XLaR125U15	125A	●	●
2XLaR125U15B		●	●
2XLaR125U15C		●	●
2XLaR160U15	160A	●	●
2XLaR160U15B		●	●
2XLaR160U15C		●	●
2XLaR200U15	200A	●	●
2XLaR200U15B		●	●
2XLaR200U15C		●	●
2XLaR250U15	250A	●	●
2XLaR250U15B		●	●
2XLaR250U15C		●	●
2XLaR300U15	300A	●	●
2XLaR300U15B		●	●
2XLaR300U15C		●	●
2XLaR315U15	315A	●	●
2XLaR315U15B		●	●
2XLaR315U15C		●	●
2XLaR350U15	350A	●	●
2XLaR350U15B		●	●
2XLaR350U15C		●	●
2XLaR400U15	400A	●	●
2XLaR400U15B		●	●
2XLaR400U15C		●	●
2XLaR420U15	420A	●	●
2XLaR420U15B		●	●
2XLaR420U15C		●	●

U15 DENOTES FOR 1500V DC

U15 表示 1500V DC

● DENOTES FOR APPROVAL

● 表示已取得安全认证

○ DENOTES FOR PENDING

○ 表示正在申请安全认证

